



MUNKEN

MUNKEN LYNX ROUGH

•

Extraordinary printing demands extraordinary design paper. The uncoated, extra tactile surface of Munken Lynx Rough and its natural white shade bring images to completion and give even more of the natural paper feel. Thanks to high bulk you can choose a lower grammage and keep thickness as well as paper stability for the best final result. Munken Lynx Rough is developed for offset print, but also suitable for various kinds of printing techniques; flexo, laser, xerography, digital printing, inkjet and for preprint applications. Also available is a crisp white, Munken Polar Rough, and a creme shaded version, Munken Pure Rough. Munken Lynx Rough standard products are available as FSC™ – The mark of responsible forestry. www.fsc.org. FSC-C022692 and PEFC certified.

MUNKEN

MUNKEN LYNX ROUGH

•

Grammage (g/m ²)	Opacity (%)	Thickness (µm)	Bulk (thickness/grammage)	Whiteness (CIE)	Brightness (ISO 2470/D65 %)	Roughness (Bendtsen, ml/min)
90	91	126	1.4	116	96	550
100	93	140	1.4	116	96	550
120	95	168	1.4	116	96	550
150	97	210	1.4	116	96	550
170	98	238	1.4	116	96	550
300^B	100	420	1.4	116	96	550

Screen recommended 133-150 lpi

^B Laminated paper

Values are targets only and can be subject to changes over time without prior notice.

MUNKEN LYNX ROUGH SPECIFICATIONS

BASIC INFORMATION



Optimized for
colour printing



Available in
sheets



Available in
reels



Uncoated



Coated



Smooth



Rough

Surface



Highwhite White Cream

Shade

ENVIRONMENT / SAFETY



FSC



PEFC



The paper is
inspected for
Nordic
Ecolabelled
printing



ECF



ISO 14001



EMAS



Paper Profile



Safety of Toys



Food contact



Age resistant
(ISO 9706)



Woodfree

PRINTING TECHNIQUES



Offset



Flexo



Laser



Inkjet
(black/white)