

Reflex[®] Translucent

white

The perfect printable
Transparent paper

202303

What for	How	Why
<p>Brochures Business cards Envelopes Cover and separator pages Posters Mailings Invitations Greeting cards Tags Packaging Handicrafts</p>	<p>Offset printing* Thermo-relief printing Hot foil stamping UV varnishes</p> <p>Oil-based and Dispersion varnishes Embossing</p> <p>Drilling and perforating</p> <p>Scoring, folding and die cutting Inkjet- and Laserprint</p>	<p>White is safe to be used with foodstuff up to 150 gsm Resistant to ageing Naturally transparent Uniform look through</p>

What exactly

Characteristics	Unit									Standards
Grammage	g/m ²	60	80	90	100	110	150	210	320	EN ISO 536
Caliper	µm	55	69	76	85	92	120	165	247	EN 20534
Volume spec.	cm ³ /g	0,9	0,85	0,85	0,85	0,85	0,8	0,79	0,77	DIN 53105
Moisture	%	7	7	7	7	7	7	7	7	EN 20287
Optical Whiteness	%	72,1	68,4	68,4	68,4	67,1	68,9	60,7	60,4	DIN 53145-2
Smoothness Bekk	sec.	27	20	17	15	13	8	15	8	DIN 53107
Transparency	%	78	76,7	74,9	73,3	72,3	67,5	58	45,8	DIN 53147



The mark of responsible forestry



Certified by the DQS:
ISO 9001
ISO 50001

*Use only with purely oxidative drying inks.
Given values are targets and are subject to alterations.
The information given is our current knowledge.
We recommend own tests before using material for the first time.