Munken Print Cream

Our aim with Munken Print Cream was to develop the ultimate book paper by combining the best properties of woodfree and wood-containing paper. Thus we have created a quality with bulk, strength, surface, readability and printability especially for book production. The result is a high quality cream shaded book paper with a feel and stiffness suited to most types of books, for colour or black and white print. Munken Print Cream comes in a wide range of bulks and grammages in sheets and reels, enabling the same quality to be used for both covers and inserts. There is also a white version: see under Munken Print White. Munken Print Cream standard products are available as FSCTM and PEFC certified.

MUNKEN PRINT CREAM 15 - (JAN 07)							
Grammage (g/m²)	70	80	90	100	115	150	300 ^b
Opacity (%)	87	89	91	92	94	96	100
Thickness (µm)	105	120	135	150	172	225	450
Bulk (thickness/grammage)	·						1.5
Whiteness (CIE)							62
Brightness (ISO 2470/D65 %)							80
Roughness (Bendtsen, ml/min)							300
Screen recommended 133-150 lpi							
FSC, PEFC, ISO 14001, Paper Profile, EMAS							
MUNKEN PRINT CREAM 18 - (DEC 09)							
Grammage (g/m²)		70	80	90	100	115	150 ^d
Opacity (%)		87	89	91	92	94	96
Thickness (µm)		124	144	162	180	209	270
Bulk (thickness/grammage)							1.8
Whiteness (CIE)							62
Brightness (ISO 2470/D65 %)							80
Roughness (Bendtsen, ml/min)							500
Screen recommended 133-150 lpi							
FSC, PEFC, ISO 14001, Paper Profile, EMAS							







MUNKEN PRINT CREAM 20 - (DEC 9)				
Grammage (g/m²)	70 ^d	80	90	100
Opacity (%)	87	89	91	92
Thickness (μm)	140	160	180	200
Bulk (thickness/grammage)				2.0
Whiteness (CIE)				62
Brightness (ISO 2470/D65 %)				80
Roughness (Bendtsen, ml/min)				1200
Screen recommended 85-133 lpi				
FSC, PEFC, ISO 14001, Paper Profile, EMAS				

Values are targets only and can be subject to changes over time without prior notice. You will find the latest valid technical specifications and information about our products at www.arcticpaper.com.







^b Laminated paper

^d Not standard production. Min. 10 tonnes and paper machine trim needed.